


Product

LP. Art Paper-A / RLY-B

Sales Code : LPAAEGC1C0 | Issued on : 15-11-2023



FACESTOCK

Color and appearance
Basis weight
Thickness
Tensile strength (MD)
Tensile strength (CD)

ART PAPER

White
80 gsm ± 4%
63 µm ± 5 µm
4.42 kg/15 mm
1.89 kg/15 mm

ADHESIVE

Description: Camel adhesive formulation is aqueous dispersion of an acrylic copolymer which is a special adhesive for label stock.

Application Test:

- 180° Peel strength test on stainless steel (FTM 1) is paper tear.
- Loop tack test (FTM 9) acceptance value min 6.0 N.
- 180° Peel strength test internal standard (PK/QC/21) min. 60 seconds.
- Service temperature range -20°C to 70°C

RELEASE LINER

Basis weight
Thickness
Tensile strength (MD)
Tensile strength (CD)
Release force label paper

WOODFREE LIGHT YELLOW WITH PE (POLYETHYLENE) LAMINATION

72 gsm ± 4%
89 µm ± 10 µm
3.69 kg/ 15 mm
7.10 kg/ 15 mm
Low release type : 0 – 15 gf

SHELF LIFE

One year when stored at room temperature (25°C; 55%RH)

OTHER INFORMATION

Total thickness: 162 µm ± 10%

Due to the wide variety of possible uses and applications, customers should determine the suitability for their specific purpose before to use.