

**Product**

**LF-VMG105-CCKP “CAMEL”**

Sales Code : LFLDFHCBC0 | Issued on : 17-01-2025



**FACESTOCK**

Thickness	0.105 mm ± 0.01 mm
Tensile strength (MD)	61.66 N/mm <sup>2</sup>
Tensile strength (CD)	41.53 N/mm <sup>2</sup>

**PVC METALIZE**

**ADHESIVE**

Description	Camel adhesive formulation is aqueous dispersion of an acrylic copolymer which is a special adhesive for label stock.
Application Test	<ul style="list-style-type: none"> <li>- 180° Peel strength test on stainless steel (FTM 1) after aging 20 minutes is 4.220 N.</li> <li>- 180° Peel strength test on stainless steel (FTM 1) after aging 24 hours is 7.105 N.</li> <li>- Loop tack test (FTM 9) acceptance value min 6.0 N.</li> <li>- Service temperature range -10°C to 70°C.</li> </ul>

**RELEASE LINER**

Basis weight	120 gsm ± 4%
Thickness	125 µm ± 10 µm
Tensile strength (MD)	10.34 kg/15 mm
Tensile strength (CD)	4.57 kg/15 mm
Release force label film	Low release type : 0 – 15 gf

**CLAY COATED KRAFT**

**SHELF LIFE**

One year when stored at room temperature (25°C; 55%RH)

**OTHER INFORMATION**

Total thickness 255 µm ± 10%

Due to the wide variety of possible uses and applications, customers should determine the suitability for their specific purpose before to use.

