

**Product**

**LF-VWG100-CCKP "CAMEL"**

Sales Code : LFLCFICBC0 | Issued on : 17-01-2025



**FACESTOCK**

Appearance  
 Thickness  
 Tensile strength (MD)  
 Tensile strength (CD)

**PVC FILM**

White, soft  
 0.10 mm ± 0.01 mm  
 40.74 N/mm<sup>2</sup>  
 38.76 N/mm<sup>2</sup>

**ADHESIVE**

Description: Camel adhesive formulation is aqueous dispersion of an acrylic copolymer which is a special adhesive for label stock.

Application Test:

- 180° Peel strength test on stainless steel (FTM 1) after aging 20 minutes is 3.945 N.
- 180° Peel strength test on stainless steel (FTM 1) after aging 24 hours is 8.854 N.
- Loop tack test (FTM 9) acceptance value min 6.0 N.
- Service temperature range -10°C to 70°C.

**RELEASE LINER**

Basis weight  
 Thickness  
 Tensile strength (MD)  
 Tensile strength (CD)  
 Release force label film

**CLAY COATED KRAFT**

120 gsm ± 4%  
 125 µm ± 10 µm  
 10.34 kg/15 mm  
 4.57 kg/15 mm  
 Low release type : 0 – 15 gf

**SHELF LIFE**

One year when stored at room temperature (25°C; 55%RH)

**OTHER INFORMATION**

Total thickness: 250 µm ± 10%

Due to the wide variety of possible uses and applications, customers should determine the suitability for their specific purpose before to use.

