

Product

LF-VWG80-CCKP-BO "CAMEL"

Sales Code : LFLARGCBC0 | Issued on : 17-01-2025



FACESTOCK

Appearance
 Thickness
 Tensile strength (MD)
 Tensile strength (CD)

PVC FILM

White, soft
 0.08 mm ± 0.01 mm
 46.16 N/mm²
 32.21 N/mm²

ADHESIVE

Description

Camel adhesive formulation is aqueous dispersion of an acrylic copolymer which is a special adhesive for label film of PVC large format containing a plasticizer-resistant that does not leave any residue on the substrate upon debonding.

Application Test

- 180° Peel strength test on stainless steel (FTM 1) after aging 20 minutes is 11.894 N.
- 180° Peel strength test on stainless steel (FTM 1) after aging 24 hours is 14.227 N.
- Loop tack test (FTM 9) acceptance value min 6.0 N.
- Service temperature range -10°C to 70°C.

RELEASE LINER

Basis weight
 Thickness
 Tensile strength (MD)
 Tensile strength (CD)
 Release force label film

CLAY COATED KRAFT

120 gsm ± 4%
 125 µm ± 10 µm
 10.34 kg/15 mm
 4.57 kg/15 mm
 Low release type : 0 – 15 gf

SHELF LIFE

One year when stored at room temperature (25°C; 55%RH)



TECHNICAL DATA SHEET

OTHER INFORMATION

Total thickness 230 $\mu\text{m} \pm 10\%$

Due to the wide variety of possible uses and applications, customers should determine the suitability for their specific purpose before to use.

