

Product

LP-BK60-RY72 “CAMEL”

Sales Code : LPKCEGC1C0 | Issued on : 17-01-2025



FACESTOCK

Basis weight	60 gsm ± 4%
Tensile strength (MD)	6.01 kg/15mm
Tensile strength (CD)	2.02 kg/15mm

KRAFT PAPER

ADHESIVE

Description	Camel adhesive formulation is aqueous dispersion of an acrylic copolymer which is a special adhesive for label stock.
Application Test	<ul style="list-style-type: none"> - 180° Peel strength test on stainless steel (FTM 1) is paper tear. - Loop tack test (FTM 9) acceptance value min 6.0 N. - 180° Peel strength test internal standard (PK/QC/21) min. 60 seconds. - Service temperature range -20°C to 70°C

RELEASE LINER

Basis weight	72 gsm ± 4%
Thickness	89 µm ± 10 µm
Tensile strength (MD)	7.10 kg/15mm
Tensile strength (CD)	3.69 kg/15mm
Release force label paper	Low release type : 0 – 15 gf

WOODFREE LIGHT YELLOW WITH PE (POLYETHYLENE) LAMINATION

SHELF LIFE

One year when stored at room temperature (25°C; 55%RH)

OTHER INFORMATION

Total thickness 183 µm ± 10%

Due to the wide variety of possible uses and applications, customers should determine the suitability for their specific purpose before to use.

