

Product

LPDP-TINTO-CCKP "CAMEL"

Sales Code : LPDTBGBCB0 | Issued on : 20-01-2025



FACESTOCK

Basis weight	90 gsm ± 4%
Tensile strength (MD)	7.96 kg/15mm
Tensile strength (CD)	2.30 kg/15mm

TINTORETO GESO

ADHESIVE

Description	Camel adhesive formulation is aqueous dispersion of an acrylic copolymer which is a special adhesive for digital printing.
Application Test	<ul style="list-style-type: none"> - 180° Peel strength test on stainless steel (FTM 1) is 9.630 N. - Loop tack test (FTM 9) acceptance value min 6.0 N. - 180° Peel strength test internal standard (PK/QC/21) min. 60 seconds. - Service temperature range -10°C to 70°C.

RELEASE LINER

Basis weight	126 gsm ± 4%
Thickness	138 µm ± 10 µm
Tensile strength (MD)	11.11 kg/15 mm
Tensile strength (CD)	5.06 kg/15 mm
Release force label film	Low release type : 0 – 30 gf

CLAY COATED KRAFT

SHELF LIFE

One year when stored at room temperature (25°C; 55%RH)

OTHER INFORMATION

Total thickness	266 µm ± 10%
Due to the wide variety of possible uses and applications, customers should determine the suitability for their specific purpose before to use.	

