

Product

LF-VMG105-CCKP “CAMEL”

Sales Code : LFLDFHCBC0 | Issued on : 17-01-2025



FACESTOCK

Thickness	0.105 mm ± 0.01 mm
Tensile strength (MD)	61.66 N/mm ²
Tensile strength (CD)	41.53 N/mm ²

PVC METALIZE

ADHESIVE

Description	Camel adhesive formulation is aqueous dispersion of an acrylic copolymer which is a special adhesive for label stock.
Application Test	<ul style="list-style-type: none"> - 180° Peel strength test on stainless steel (FTM 1) after aging 20 minutes is 4.220 N. - 180° Peel strength test on stainless steel (FTM 1) after aging 24 hours is 7.105 N. - Loop tack test (FTM 9) acceptance value min 6.0 N. - Service temperature range -10°C to 70°C.

RELEASE LINER

Basis weight	120 gsm ± 4%
Thickness	125 µm ± 10 µm
Tensile strength (MD)	10.34 kg/15 mm
Tensile strength (CD)	4.57 kg/15 mm
Release force label film	Low release type : 0 – 15 gf

CLAY COATED KRAFT

SHELF LIFE

One year when stored at room temperature (25°C; 55%RH)

OTHER INFORMATION

Total thickness	255 µm ± 10%
Due to the wide variety of possible uses and applications, customers should determine the suitability for their specific purpose before to use.	

