

Product

LF. VTS60-RY128P "CAMEL"

Sales Code : LFPHDHD1C0 | Issued on : 21-01-2025



FACESTOCK

Color and appearance
 Thickness
 Tensile strength (MD)
 Tensile strength (CD)

PVC FILM

Transparent soft
 0.06 mm ± 0.01 mm
 26.20 N/mm²
 40.51 N/mm²

ADHESIVE

Description

Camel adhesive formulation is aqueous dispersion of an acrylic copolymer which is a special adhesive for label stock.

Application Test

- 180° Peel strength test on stainless steel (FTM 1) is 12.580 N.
- Loop tack test (FTM 9) acceptance value min 6.0 N.
- 180° Peel strength test internal standard (PK/QC/21) min. 60 seconds.
- Service temperature range -10°C to 70°C

RELEASE LINER

Basis weight
 Thickness
 Tensile strength (MD)
 Tensile strength (CD)
 Release force label film

WOODFREE YELLOW WITH PE (POLYETHYLENE) LAMINATION

128 gsm ± 4%
 156 µm ± 10 µm
 13.48 kg/15mm
 7.01 kg/15mm
 Low release type : 0 – 15 gf

SHELF LIFE

One year when stored at room temperature (25°C; 55%RH)

OTHER INFORMATION

Total thickness 226 µm ± 10%

Due to the wide variety of possible uses and applications, customers should determine the suitability for their specific purpose before to use.

