

**Product**

**LF. DP-PPTR50-CCKP-IND "CAMEL"**

Sales Code : LFDLDHCBC0 | Issued on : 21-01-2025



**FACESTOCK**

Color and appearance  
 Thickness  
 Tensile strength (MD)  
 Tensile strength (CD)

**BOPP (BIAXIALLY ORIENTED POLYPROPYLENE) FILM**

Transparent film with special treatment for HP Indigo  
 50  $\mu\text{m} \pm 3 \mu\text{m}$   
 121.3  $\text{N}/\text{mm}^2$   
 266.5  $\text{N}/\text{mm}^2$

**ADHESIVE**

Description  
 Camel adhesive formulation is aqueous dispersion of an acrylic copolymer which is a special adhesive for digital printing.

Application Test

- 180° Peel strength test on stainless steel (FTM 1) is 9.080 N.
- Loop tack test (FTM 9) acceptance value min 6.0 N.
- 180° Peel strength test internal standard (PK/QC/21) min. 60 seconds.
- Service temperature range -10°C to 70°C

**RELEASE LINER**

Basis weight  
 Thickness  
 Tensile strength (MD)  
 Tensile strength (CD)  
 Release force label film

**CLAY COATED KRAFT**

126  $\text{gsm} \pm 4\%$   
 138  $\mu\text{m} \pm 10 \mu\text{m}$   
 11.11  $\text{kg}/15 \text{ mm}$   
 5.06  $\text{kg}/15 \text{ mm}$   
 Low release type : 0 – 30 gf

**SHELF LIFE**

One year when stored at room temperature (25°C; 55%RH)

**OTHER INFORMATION**

Total thickness 205  $\mu\text{m} \pm 10\%$   
 Total grammage 200  $\text{gsm} \pm 5\%$   
 Paper type 160  $\text{gsm}$

Due to the wide variety of possible uses and applications, customers should determine the suitability for their specific purpose before to use.

