

**Product**

**LF. VWR80-BCP "CAMEL"**

Sales Code : LFPGBHBAC0 | Issued on : 20-01-2025



**FACESTOCK**

Color and appearance  
 Thickness  
 Tensile strength (MD)  
 Tensile strength (CD)

**PVC FILM**

Milky white rigid  
 0.08 mm ± 0.01 mm  
 71.68 N/mm<sup>2</sup>  
 55.22 N/mm<sup>2</sup>

**ADHESIVE**

Description

Camel adhesive formulation is aqueous dispersion of an acrylic copolymer which is a special adhesive for label stock.

Application Test

- 180° Peel strength test on stainless steel (FTM 1) is 10.573 N.
- Loop tack test (FTM 9) acceptance value min 6.0 N.
- 180° Peel strength test internal standard (PK/QC/21) min. 60 seconds.
- Service temperature range -10°C to 70°C

**RELEASE LINER**

Basis weight  
 Thickness  
 Tensile strength (MD)  
 Tensile strength (CD)  
 Release force label film

**BRIEFFCARD PE LAMINATED**

165 gsm ± 4%  
 205 µm ± 10 µm  
 12.97 kg/15mm  
 6.40 kg/15mm  
 Low release type : 0 – 15 gf

**SHELF LIFE**

One year when stored at room temperature (25°C; 55%RH)

**OTHER INFORMATION**

Total thickness 311 µm ± 10%

Due to the wide variety of possible uses and applications, customers should determine the suitability for their specific purpose before to use.

