

Product

LF. VWS80-BCP " CAMEL "

Sales Code : LPPEGBAC0 | Issued on : 21-01-2025



FACESTOCK

Color and appearance
 Thickness
 Tensile strength (MD)
 Tensile strength (CD)

PVC FILM

Milky white soft
 0.08 mm ± 0.01 mm
 30.84 N/mm²
 31.32 N/mm²

ADHESIVE

Description: Camel adhesive formulation is aqueous dispersion of an acrylic copolymer which is a special adhesive for label stock.

Application Test:

- 180° Peel strength test on stainless steel (FTM 1) is 12.267 N.
- Loop tack test (FTM 9) is 8.841 N (Acceptance value min 6.0 N).
- 180° Peel strength test internal standard (PK/QC/21) is 654 seconds (min. 60 seconds).
- Service temperature range -10°C to 70°C

RELEASE LINER

Basis weight
 Thickness
 Tensile strength (MD)
 Tensile strength (CD)
 Release force label film

BRIEFFCARD PE LAMINATED

165 gsm ± 4%
 205 µm ± 10 µm
 12.97 kg/15mm
 6.40 kg/15mm
 Low release type : 0 – 15 gf

SHELF LIFE

One year when stored at room temperature (25°C; 55%RH)

OTHER INFORMATION

Total thickness: 306 µm ± 10%

Due to the wide variety of possible uses and applications, customers should determine the suitability for their specific purpose before to use.

