

**Product**

**LFDP-PETMM36-CCKP "CAMEL"**

Sales Code : LFDRDHCBC0 | Issued on : 20-01-2025



**FACESTOCK**

Color and appearance  
 Thickness  
 Tensile strength (MD)  
 Tensile strength (CD)

**PET METALIZE MATT**

Metalize film with special treatment for digital printing  
 36  $\mu\text{m} \pm 3 \mu\text{m}$   
 126.03 N/mm<sup>2</sup>  
 104.36 N/mm<sup>2</sup>

**ADHESIVE**

Description: Camel adhesive formulation is aqueous dispersion of an acrylic copolymer which is a special adhesive for label stock.

Application Test:

- 180° Peel strength test on stainless steel (FTM 1) is 8.147 N.
- Loop tack test (FTM 9) acceptance value min 6.0 N.
- 180° Peel strength test internal standard (PK/QC/21) min. 60 seconds.
- Service temperature range -10°C to 70°C.

**RELEASE LINER**

Basis weight  
 Thickness  
 Tensile strength (MD)  
 Tensile strength (CD)  
 Release force label film

**CLAY COATED KRAFT**

126 gsm  $\pm 4\%$   
 138  $\mu\text{m} \pm 10 \mu\text{m}$   
 11.11 kg/15 mm  
 5.06 kg/15 mm  
 Low release type : 0 – 30 gf

**SHELF LIFE**

One year when stored at room temperature (25°C; 55%RH)

**OTHER INFORMATION**

Total thickness: 192  $\mu\text{m} \pm 10\%$   
 Total grammage: 186 gsm  $\pm 5\%$   
 Paper Type: 160 gsm

Due to the wide variety of possible uses and applications, customers should determine the suitability for their specific purpose before to use.

